

# MOBILITY ROW CROP SPREADERS



**MOBILITY 600**



**MOBILITY 800**

## MOBILITY SPREADER FEATURES:

- Box material and gussets all stainless steel above the frame.
- Adjustable single axle - 78" to 120".
- 540/1000 PTO dual drive system.
- The two speed conveyor drive system allows for a wide range of application rates.
- Dual spinner with bolt on blades.
- Safety guard around fans.
- Hitch with heavy duty adjustable clevis.
- Safety chain.
- 5000 pound swivel jack.
- Ground clearance 40" under spinners and 47" under frame.
- Agri-Cover SRT manual roll tarp.

## MOBILITY 600 SPECIFICATIONS:

- 200 cubic foot capacity.
- Heavy duty 8 bolt hubs with 3" spindles.
- 12.4 x 42" tires.
- Overall height: 112"
- Overall length: 203"

## MOBILITY 800 SPECIFICATIONS:

- 270 cubic foot capacity.
- Sight window in front of hopper.
- Hydraulic on/off for conveyor drive.
- Heavy duty 10 bolt hubs with 3 1/2" spindles.
- 14.9 x 46" tires.
- Overall height: 116"
- Overall length: 215"



Billings, MT ~ Valley City, ND ~ Yakima, WA  
Phone: 800-437-9702 ~ Fax: 800-313-3299  
[www.feiinc.com](http://www.feiinc.com)