

QUALITY STEEL CORPORATION

FEI, Inc. is a distributor of Quality Steel Corporation tanks.



WATER CAPACITY	DIAMETER (OD)	OVERALL LENGTH	WEIGHT (lbs.)
120 wg.	24"	5'-8"	260
250 wg.	30"	7'-10"	480
320 wg.	30"	9'-7"	620
500 wg.	37-1/2"	10'	950
1000 wg.	41"	16'	1,800
1450 wg.	46-1/2"	17'-4"	2,650
1990 wg.	46-1/2"	23'-11"	3,520

Dimensions and specifications shown are approximate. Individual vessels may vary.

- Conforms to the latest edition of ASME Rules for Construction of Pressure Vessels, Section VIII, Division 1. Complies with NFPA 58.
- Rated at 250 psig from -20° F to 125° F. All vessels register with National Board.
- Two Service options available:
 - Option 1:** Ready-to-bury underground option, coated with either powder coated phenolic epoxy finish or liquid applied epoxy primer coat followed by urethane top coat, supplied with composite AG/UG dome.
Underground Sizes Available: 120, 250, 500 and 1000 gallon, other sizes available via special order.
 - Option 2:** Aboveground option, coated with either powder coated TGIC polyester finish or liquid applied epoxy primer coat followed by urethane top coat, supplied with steel AG/UG dome.
Aboveground Sizes Available: 120, 250, 500 and 1000 gallon, other sizes available via special order.
- All vessels are shipped vacuum pre-purged to enable simplified first fill of the vessel.



THE PRODUCTS, KNOWLEDGE, AND EXPERIENCE TO SERVE YOUR NEEDS!

Billings, MT | Hastings, NE | Valley City, ND | Yakima, WA
Phone: 800-437-9702 | Fax: 800-313-3299 | www.feinc.com