



# Conveyor Belting and Splicing

A complete line of elevator and conveyor belting is available in a variety of styles including PVC, rubber and FDA approved food grade. All belts can be supplied slit, cut to length and punched to your requirements. A range of splices have been designed to handle any application.



**NEW, REPLACE OR REPAIR**

FEI is your source for conveyor belting.

- New belting
- Replacement belting
- Belting repair
- Custom lengths
- Full lacing service
- Same day shipping

**Crescent Top™** conveyor belting features an overlapping crescent design for conveying loose and non-rigid materials. It offers maximum product holding power and the crescents may be inverted for easy drainage. The crescent design minimizes noise levels and belt wear by its smooth movement over return rollers. This belting has a temperature rating to -40° F.

PART NUMBER	DESCRIPTION
201818	18" Crescent Belting - 120 PVC
201824	24" Crescent Belting - 120 PVC
201830	30" Crescent Belting - 120 PVC
201836	36" Crescent Belting - 120 PVC

**Conveyor Parts and Accessories**



2 PLY 220 RUBBER	3 PLY 330 RUBBER
Strength: 220 PIW	Strength: 330 PIW
Thickness: 0.270 in.	Thickness: 0.312 in.
Weight: 0.132 lbs. PIW	Weight: 0.157 lbs. PIW
Min. Pulley Diameter: 12 in.	Min. Pulley Diameter: 14 in.
Temp. Range: -30°F to 200°F	Temp. Range: -30°F to 200°F
Max. Bucket Projection: 6 in.	Max. Bucket Projection: 8 in.

More belt types available, contact FEI for information.

**800-437-9702 | feiinc.com**

Delivering solutions to fuel and feed the world.