



Sonariot Tank Monitors



Sonar technology that accurately measures tank liquid levels on all single-wall above ground tanks.

- Accuracy within $\pm 1\%$ of actual tank level
- Sensors work on all single-wall above ground tanks
- Use on pressurized or non-pressurized tanks
- Easy magnetic mount installation
- Remote inventory tracking in real-time
- Operating temperature range of -55° to 140° F.



Use for Propane, Butane, Oil, Chemical, Water, Beverages and more.



The Sonariot Advantage[®] allows you to monitor tank liquid levels from a smartphone, tablet or computer. Sensors available for 20 lb. cylinders up to 60,000 gallon pressurized and non-pressurized storage tanks.

Sonariot Sensor Types

Pro-Plus Sensors

For Pressurized Tanks

- Magnetic mount
- Non-invasive
- Accuracy $\pm 1\%$
- 2G-4G Global Sim
- Role based mobile application
- Management Dashboard
- Bulk data available via API
- High tech convenience that pays for itself

Pro Sensors

For Pressurized Tanks

- Magnetic mount
- Non-invasive
- Accuracy $\pm 1\%$
- Bluetooth communication
- Mobile application
- Use on 20 lb. cylinder up to 1,000 gallon horizontal tank to monitor your own tank levels
- Compatible with Mopeka WiFi Bridge

TD-40 Sensors

For Non-Pressurized Tanks

- Easy installation
- Compatible with 2.5" fill ports
- Non-invasive
- Accuracy $\pm 1\%$
- 2G-4G Global Sim
- Role based mobile application
- Management Dashboard
- Bulk data available via API
- High tech convenience that pays for itself

Pressurized Tanks



LP-854069008251 Pro-Plus Residential Sensor mounts to the bottom of aluminum or steel, horizontal or vertical tanks that are less than 1,000 gallons and less than 48" diameter.



LP-854069008282 Pro-Plus Bulk/Commercial Sensor mounts to the bottom of aluminum or steel, horizontal or vertical tanks that are greater than 1,000 gallons and diameters 132" and below.



LP-854069008220 Bluetooth enabled, Standard Pro Sensor mounts to the bottom of aluminum or steel, horizontal or vertical tanks from 20 lb. up to 1,000 gallon horizontal. The sensor comes in a metal tin along with a grease pack and tank spacers. Use to monitor your own tank levels.

Non-Pressurized Tanks



LP-854069008329 TD40 Residential Sensor mounts to the top of any tank orientation with a depth up to 48".



LP-854069008343 TD40 Bulk Sensor mounts to the top of any tank orientation with a depth up to 132".

Delivering solutions to fuel and feed the world.

Call 800-437-9702 or Shop Online at feinc.com