DURA-ABSTM AUTO-BATCH SYSTEM

PRODUCT SPECIFICATIONS



	APR logy wit		

Operating Temp	-10°F to 130°F	
Flow Rate	Up to 15GPM	
Meter Accuracy	+/5%	
Backlit LCD Display	Yes; with back-light timeout	
Max Pressure	40 psi	
Pump Ports	In: 1" FNPT x 2" MNPT; Out: 1" FNPT	
Units Measured	Gallons / Liters / Ounces	
Chemically Resistant	Yes, EPDM, Viton® or Silicone seals	
Calibration	Preset, Quick List or Manual	
Mounting Range	Fixed or In-line	
Vibration / Shock Resistant	Yes	
EPA Compliant	Yes, 165.45	

Always turn pump off and disconnect system from power when not in use.

How It Works

Select the volume desired

Press START

Employee Owned

3 The pump will begin to dispense luid then automatically shut off when complete

- / Intuitive interface allows for the selection of manual or automatic operation with the flip of a switch
- / High-flow pump with up to 15GPM/56LPM flow rate /
- Optimized for repeatable batching; returns to the last volume amount dispensed
- / 100% moisture-sealed circuitry

U 00

- / Includes Dura-Meter[™] with impact resistant Lexan[™] faceplate
- / Available in 12 Volt or 110 Volt, and EPDM, Viton® or Silicone options
- / Includes a 2-year Warranty and Maintenance Program
- / Measures in gallons, liters and ounces

DPABS-4312E	DPABS-4312V	DPABS-4312S			
EPDM 12 Volt	Viton [®] 12 Volt	Silicone 12 Volt			
DPABS-4315E	DPABS-4315V	DPABS-4315S			
EPDM 110 Volt	Viton [®] 110 Volt	Silicone 110 Volt			

800-437-9702 | feiinc.com

THE PRODUCTS, KNOWLEDGE AND EXPERIENCE TO SERVE YOUR NEEDS!

The industry's **ONLY transfer system** offering an automated dispensing option.



- **DURA-ABS**TM AUTO-BATCH SYSTEM
- / Intuitive interface allows for the selection
- of manual or automatic operation with the flip of a switch
- / High-flow pump with up to 15GPM/56LPM flow rate
- / Optimized for repeatable batching; returns to the last volume amount dispensed
- /100% moisture-sealed circuitry
- / Includes Dura-Meter[™] with impact resistant Lexan[™] faceplate
- / Available in 12 Volt or 110 Volt, and EPDM, Viton[®] or Silicone options
- / Includes a 2-year Warranty & Maintenance Program
- / Measures in gallons, liters and ounces



- Select the volume desired
- Press START
- 3 The pump will begin to dispense luid then automatically shut off when complete

FEI Employee Owned

800-437-9702 | feiinc.com

THE PRODUCTS, KNOWLEDGE AND EXPERIENCE TO SERVE YOUR NEEDS!